

Flight Test of the F/A-18 Active Aeroelastic Wing Airplane

David Voracek

Presenting

the

Flight Test Analysis and Evaluation done by:


Robert Clarke,

Michael J. Allen, Ryan P. Dibley,

John Hodgkinson and Joseph Gera

NASA Dryden Flight Research Center

Explore. Discover. Understand.




F/A-18 AAW Airplane




NASA Photo: EC04-0361-08


Explore. Discover. Understand.



F/A-18 AAW Control Surfaces




Explore. Discover. Understand.




Flight Test Background


- Phase I - from Nov 02 to Jun 03
 - Flutter clearance, air data calibration, aerodynamic and loads model development
- Phase II - from Dec 04 to Mar 05
 - Boeing & DFRC CLAW designs
- Phase IA - Mar 05
 - Aeroservoelastic research
- Phase IIA - Mar 05
 - CLAW's at several test points were redesigned




Roll Control Effectiveness Regions




Explore. Discover. Understand.



AAW Design Test Points




Explore. Discover. Understand.




AAW Phase I Test Maneuvers

- OBES ASE/flutter clearance
- Air data calibration
 - Tower flyby
 - Level accel's
 - POPU's
 - Slow β sweeps
- Simulated OLEF failure (left OLEF)
- OBES pitch and roll doublets
- Demonstration maneuvers
 - 5-g WUT
 - 1-g bank-to-bank/360° rolls (incremental build-up to full stick or load limit)
 - 4-g RPO


Explore. Discover. Understand.




OBES Pitch Doublets




Explore. Discover. Understand.







OBES Roll Doublets




Explore. Discover. Understand.



AAW Aileron Flexibility




Explore. Discover. Understand.




Phase I - Lessons Learned

- Phase I flight tests using OBES provided good data for aerodynamic and loads model development, but hindsight showed some of the doublet maneuvers were too small
- Phase I results showed no tendency for aileron reversal (flexibility of the aileron may have contributed to this)
- The AAW airplane was unable to accomplish any testing at two of the highest dynamic pressure test points
- Aileron hinge moment loads were a design driver for the Phase II CLAW's


Control Law Development and Verification & Validation Testing




- Both Boeing and NASA DFRC teams developed control laws for each design test point
 - Boeing used ISMD design process
 - NASA used CONDUIT® design process
- Verification testing and limited validation testing conducted by Boeing (FAST and piloted HIL)
- Extensive HIL V&V testing conducted at DFRC
 - Aerodynamic modeling issues were examined for safety-of-flight
 - IADS displays were used as part of test (built confidence in them before they were used for flight test)
 - Several errors in the flight code caught and fixed
 - Rudder trim gain had incorrect value
 - Transient free switches caused control surfaces to drift



AAW Phase II RFCS Envelopes




Explore. Discover. Understand.







AAW 1-g Phase II Flight Test


- 1-g bank to bank and 360° rolls
 - Tested the primary AAW technology (ability to roll the airplane using only wing control surfaces)
 - Tested the ability of the control laws to achieve acceptable roll performance and flying qualities while maintaining loads within limits
- Learned how well the aerodynamic and loads models predicted the vehicle's response (issues were linearity and superposition)




Region I - Subsonic 1-g Rolls




Explore. Discover. Understand.







Region I - Subsonic 1-g 360° Roll




Explore. Discover. Understand.




Region II - Supersonic 1-g Rolls




Explore. Discover. Understand.







Region II - Supersonic 1-g 360° Roll




Explore. Discover. Understand.




Region III - Subsonic 1-g Rolls




Explore. Discover. Understand.





Region III - Subsonic 1-g 360° Roll



Explore. Discover. Understand.




Roll Axis HOS/LOS Comparison Region II - Supersonic (open-loop)





$\tau=0.25$

Explore. Discover. Understand.




Roll Axis HOS/LOS Comparison Region II - Supersonic (closed-loop)




$\tau = 0.22$

Explore. Discover. Understand.


AAW Phase II Elevated-g Flight Test




- Windup Turn
 - Tested the ability of the control law designs to reduce wing loads (maneuver load control) or replicate basic F/A-18 trim schedules
- Rolling Pull Out
 - Tested the primary AAW technology (ability to roll the airplane using only wing control surfaces)
 - Tested the ability of the control laws to achieve acceptable roll performance and flying qualities while maintaining loads within limits
- Learned how well the aerodynamic and loads models predicted the vehicle's response (issues were linearity and superposition)




Region I - Subsonic 4-g RPO




Explore. Discover. Understand.



Region I - Subsonic 4-g RPO



Explore. Discover. Understand.



Phase II - Lessons Learned

- The RFCS worked well in both Phases I and Phase II
- The AAW program was the first program at DFRC to utilize a RFCS in a safety of flight critical envelope
- The IADS[®] displays worked well for safety monitoring
- Comparison of the flight data and predicted airplane response ranged from fair to excellent